

QuickFit™ 2-way 8" ceiling speaker with TwistFix™ grill

Highlights:

- Exceptional intelligibility and musical performance
- TwistFix™ borderless grill design
- Lifetime stability and toolfree installation with unique Quickfit™ innovation
- Excellent off axis performance
- Flat frequency response
- Consistent sound profile throughout complete family

Product information:

Designed to offer the best value for money ratio. The CIRA series are coaxial 2-way ceiling speakers featuring exceptional intelligibility and musical performance. The TwistFix™ borderless grill design offers easy but solid assembly and a completely seamless transition from grill to ceiling. This results in a perfect blend in to its environment. The QuickFit™ installation system combined with FastCon™ connector offers lifetime stability and great installers convenience.

The CIRA8 features a 8" driver using polypropylene cone material, combined with a 1" Mylar tweeter fitted with a phase plug for excellent off axis performance. The selected materials guarantee a low distortion performance with smooth and flat frequency response. A continuous power handling of 40 Watt (RMS) and maximum power handling of 80 watt is achieved, while fitted with a multi-tapping 100V line transformer with tapings for 24W, 12W, 6W and an 8 Ohm & 16 Ohm bypass connection.

Applications:

- Corporate
- Retail
- Bars & Restaurants



Impedance:

Ω 8 Ohm Ω 16 Ohm

Voltage:

 100 Volt

System specifications:

Peak power handling		160 W
Program power handling		80 W
Continuous power (AES)		40 W
Sound Pressure (Max. W/1m)	@ 100 V	105 dB
Sensitivity (1W/1m)		89 dB
Frequency	Response (± 3 dB)	40 Hz - 20 kHz
Speaker type		2-way coaxial
Impedance		8 Ω (CIRA824) 16 Ω (CIRA840D)
Frequency	Range (-10 dB)	33 Hz - 20 kHz
Dispersion	Conical	140°
Connectors		Multi-tap Fast-con™ connections
Drivers	HF	1"
	LF	8"
Line Transformer Tappings	1	24 W - 417 Ω (CIRA824)
	2	12 W - 833 Ω (CIRA824)
	3	6 W - 1667 Ω (CIRA824)

Product Features:

Cut-out measurement		9.57 " (\emptyset)
Dimensions		10.63 x 3.23 " (\emptyset x D)
Weight		3.64 lb (CIRA840D) 3.86 lb (CIRA824)
Operating temperature		-20 °C ~ 60 °C
Construction		ABS
Front finish		Twist-Fix™ borderless finely perforated steel grill
Built-in depth		3.23 "
Mounting		QuickFit™ mounting system
Colours		White (RAL9003) (CIRA824/W & CIRA840D/W)

Variants:

- CIRA840DI/W - White version, 16 Ω (RAL9016)
- CIRA824I/W - White version, 8 Ω & 24 Watt @ 100V (RAL9016)