

Highlights:

- Lightweight class-D amplifier
- Advanced protection circuit
- Speakon compatible & terminal block output connections
- Energy-star certified
- Standby energy saving mode
- Convection cooled
- XLR input connections with crossover operation mode switch



Product information:

This energy efficient stereo amplifier will automatically switch to a standby mode when no audio signals are detected (less than 1Watt power consumption in standby mode). Their weight and compact size makes these single rack space amplifiers ideal for both fixed and mobile installations. Their use of Class-D technology ensures excellent efficiency as well as outstanding sound quality. Thanks to the complete passively cooled entity only a minimal of maintenance is needed, while ensuring maximum reliability. Various specific functions and advanced circuitry guarantees an optimal protection against DC malfunctioning, short circuit, overheating and overload. Signal input connections are integrated with balanced XLR connectors, and signal link through is possible using the XLR output connectors. Outputs are connected using terminal block connectors.



Applications:

- Bars & Restaurants
- Education
- Corporate
- Clubs
- Events
- Retail



Certification:

System specifications:

Continuous power (AES)	@ 4 Ω Stereo	2 x 500 W
	@ 8 Ω Stereo	2 x 300 W
	@ 8 Ω Bridge	1000 W
Frequency	Response (± 3 dB)	20 Hz - 20 kHz
Signal / Noise		> 90 dB
THD+N (@ 1 kHz)		< 0.1%
Crosstalk (@ 1 kHz)		> 70 dB
Technology		Class-D
Power	Supply	Switching mode
		AC Input: 100-120V/220-240V~ 50/60Hz

Note: Standard voltage and frequency of electricity varies from country to country. Please contact your local distributor to ensure suitable product variant voltage and frequency compatibility.

Consumption	426 W
Standby	0.7 Watt (30 min standby time)
Inputs	Sensitivity
	0 dB (1V RMS)
	Impedance
	12 kΩ balanced
	Connector
	XLR female with Male Linkthrough
Protection	DC Short circuit
	Over heating
	Over load
	Signal limiting
Cooling	Convection cooled
Operating temperature	0° ~ 40° @ 95% Humidity
Outputs	Connector
	Speakon compatible & 2-pin Euro Terminal Block (5.08 mm)

Product Features:

Dimensions	482 x 44 x 330 mm (W x H x D)
Weight	4.700 kg
Mounting	19"
Unit height	1 HE
Construction	Steel
Colours	Black