

Highlights:

- High quality back electret condenser capsule with cardioid pickup pattern
- Level & status indication LED's
- Tilttable pipe-neck microphone
- SurfaceTouch™ front panel
- Capacitive & illuminated selection buttons (8x)

Product information:

The MPX series are paging microphones specifically designed for use in combination with MTX series audio matrix systems. The MPX88 is the 8-zone system allowing it being used in combination with an MTX88 8-zone audio matrix system. The modern shaped enclosure is finished with a real glass front panel provided with an anti-glare coating. This offers a microphone with elegant outlook which will be appreciated in any office or even design interior environment. The controls are integrated in the glass panel through capacitive touch button principle without any mechanically moving parts, same as the indicator LED's which are completely blended. This guarantees a real high-end outlook and user experience. An integrated chime tone is audible before each announcement. Announcements are made through the integrated pipe-neck microphone with a cardioid pickup pattern, which can be tilted to the desired angle. Both zone selection and data bus indicators are implemented, giving an overview of the systems current operation mode and data bus occupation. Quick operation is made possible using the 'select' & 'clear all' buttons, while the 'push-to-talk' (PTT) button must be pressed during announcements. Connection to the matrix system is done through a fixed connection cable with a length of 2 meter. This distance can be extended to a maximum length of 300m using standard CAT5E (or better) twisted pair cabling. Cascading multiple paging stations is possible using the priority-based (user-configurable) databus, when using the additional junction box ARJ03P.



Applications:

- Corporate
- Sporting facilities

System specifications:

| | | |
|----------------------------|------------------------|-------------------------|
| Microphone | Type | Back electret condenser |
| | Length | 9.84 " |
| Frequency | Response (\pm 3 dB) | 50 Hz - 16 kHz |
| Sensitivity (1W/1m) | | 45 dB |
| Sound Pressure (Max. W/1m) | | 130 dB |
| Power | Consumption | 1.5 W |
| | Supply | 24 V DC (from MTX) |
| Connectors | | RJ45 (Fixed 2 m cable) |
| Polar Pattern | | Cardioid |

Product Features:

| | | |
|--------------|----------|----------------------------------|
| Dimensions | | 8.72 x 1.69 x 4.39 " (W x H x D) |
| Weight | | 0.73 lb |
| Construction | | ABS |
| Databus | Control | RS-485 |
| | Audio | Differential analogue |
| Colours | | Black (RAL9004) |
| Paging Zones | | 8 Zones (use with MTX88) |
| Accessories | Included | Windscreen |
| | | Connection cable 2 meter(fixed) |