

Highlights:

- Terminal block connection
- 2.5" LCD display with intuitive user interface
- unbalanced stereo line input

Product information:

The MWX65 is an all-in-one wall panel controller to be used in combination with the AUDAC MTX series multi-zone audio matrix systems. It can control the input signal and volume for one zone and also contains an additional line and microphone level input which can be patched to the zone it is connected to. Both input selection and volume control as well as two band tone control can be controlled using the versatile rotatable push-dial while the integrated 2.5" graphical display ensures a user friendly experience. An XLR connector is provided as additional microphone input while the line input is performed using RCA connectors. The signals applied to these inputs can be used as one additional local input. This enables you to connect any CD or MP3 player as local music source or connect a microphone for speeches or other announcements. The input mixing can be done by using both push-lock potentiometers. The microphone input has the possibility to provide 12V phantom power which can be turned on and off by software configuration. The wiring between the matrix and the wall panel should be performed by using standard UTP CAT5 cabling which transfers both the control and audio signals to the matrix while providing the power supply for the wall panel.

Applications:

- Residential
- Corporate
- Retail
- Hotels
- Bars & Restaurants



System specifications:

Control			RS-485
Audio transfer			Analogue differential (Dual mono)
Phantom Power			12 V DC (software enabling)
Cabling			CAT5 (up to 300 meter)
Display	Type		2.5" Graphical Full colour
Power	Consumption		1.8 W - 75 mA / 24 V
Connectors			8-pin Euro Terminal Block
Inputs	Unbalanced Stereo	Connector	RCA
		Sensitivity	-12 dBV ~ 12 dBV
		THD+N (@ 1 kHz)	< 0.05 %
		Signal / Noise	85 dB
	Balanced Microphone	Connector	XLR female
		Sensitivity	-50 dBV ~ -15 dBV
		THD+N (@ 1 kHz)	< 0.1%
		Signal / Noise	75 dB

Product Features:

Dimensions			6.024 x 3.70 x 1.77 " (W x H x D)
Built-in depth			1.46 "
Weight			0.46 lb
Construction			ABS
Colours			Black (RAL9005) (MWX65/B)
			White (RAL9010) (WMX65/W)
Accessories	Optional	Flush mount Installation boxes	WB5065/FS: Concrete & Brick walls
			WB5065/FG: Wooden & Gypsum walls
		Surface mount Installation boxes	WB5065/SW: White version
			WB5065/SB: Black version

Variants:

- MWX65/B - Black version
- MWX65/W - White version