

Highlights:

- 1" Dome tweeter
- 8" Low frequency loudspeaker
- Aluminum mounting bracket (MK2 version)
- Aluminum grill
- AWX5™ waterproof connector
- Vertical and horizontal mounting
- Multi-tapping 70V / 100V line transformer

Product information:

The WX802/O is a powerful 2-way performance speaker which is specially designed for outdoor use, ensuring true-to-nature, high fidelity reproduction of music and speech. It lends itself to a wide variation of outdoor applications, ensuring a clear and powerful sound reproduction. Hereby, the WX802/O is the perfect companion for outdoor applications where clear background music is desirable throughout the day and a more powerful sound with deeper bass is necessary when the party erupts after sunset. The sound is coming from a weatherproof treated 8" low-frequency loudspeaker in combination with a 1" dome tweeter which is built in an aesthetical and solid synthetic enclosure.

The material used for the mounting bracket on the outdoor versions has been improved by using aluminum, making the WX series MK2 even more resistant to extreme weather conditions. The bracket allows users to mount the WX802/O vertically as well as horizontally.

Special treatment with powder coating provides the necessary protection for all weather conditions. Because of this, the brackets can pass the 96 hours salt-spray test. A drain hole behind the aluminum front grill allows letting the moisture flow out when condensation occurs. The waterproof AWX-5 connector at the backside makes sure that this speaker meets the IP55 standards.

Applications:

- Corporate
- Retail
- Sporting facilities
- Bars & Restaurants
- Museums & Themeparks



Certification:



IP55

Properties:



Weatherproof

Impedance:



16 Ohm

Voltage:



70-100 Volt

System specifications:

Speaker type	2-way	
Peak power handling	280 W	
Program power handling	140 W	
Continuous power (AES)	70 W	
Impedance	16 Ω	
Sensitivity (1W/1m)	89 dB	
Sound Pressure (Max. W/1m)	@ 16 Ω	108 dB
	@ 100 V	106 dB
Frequency	Response (± 3 dB)	60 Hz - 17 kHz
	Range (-10 dB)	50 Hz - 20 kHz
Crossover	Frequency	2.4 kHz
	Type	Passive built-in
Dispersion	Horizontal	110°
	Vertical	110°
Ingress Protection rating	IP55	
Connectors	Waterproof AWX-5 connector	
Drivers	HF	1"
	LF	8"
Line Transformer Tappings	1	83 Ω - 100 V / Not used - 70 V / 60 W
	2	167 Ω - 100 V / 60 W - 70 V / 30 W
	3	333 Ω - 100 V / 30 W - 70 V / 15 W

Product Features:

Dimensions	10.63 x 14.17 x 8.46 " (W x H x D)					
Weight	16.53 lb					
Operating temperature	-25 °C ~ 70 °C					
Construction	ABS					
Mounting & handling	Mounting bracket					
Front finish	Aluminium grill					
Colours	Black (RAL9005) (WX802MK2/OB)					
	White (RAL9003) (WX802MK2/OW)					
Accessories	<table><tr><td>Included</td><td>Mounting bracket</td></tr><tr><td></td><td>5-pin connection cable (70 cm) AWC07</td></tr></table>	Included	Mounting bracket		5-pin connection cable (70 cm) AWC07	
Included	Mounting bracket					
	5-pin connection cable (70 cm) AWC07					
	<table><tr><td>Optional</td><td>AWC07 - AWX5 cable 0.7 m</td></tr><tr><td></td><td>AWC25 - AWX25 cable 2.5 m</td></tr></table>	Optional	AWC07 - AWX5 cable 0.7 m		AWC25 - AWX25 cable 2.5 m	
Optional	AWC07 - AWX5 cable 0.7 m					
	AWC25 - AWX25 cable 2.5 m					
	<table><tr><td></td><td>AWC50 - AWX50 cable 5 m</td></tr></table>		AWC50 - AWX50 cable 5 m			
	AWC50 - AWX50 cable 5 m					

Variants:

- WX802MK2/OB - Outdoor black version
- WX802MK2/OW - Outdoor white version